



### **SCHNEIDER EUROPEAN PRIZA, NEW UNICA,2P, 10 A, 2 MODULE, BEJ**

Schneider Electric New Unica socket-outlet NU303344 is a mechanism in color beige. The outlet pole configuration of this socket-outlet is 2P with shutters, ensuring safety protection. And this device is European standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 16A. The fixing mode of this device is clip-in. It is 45 mm in width, 45 mm in height and 37 mm in depth. With an embedding depth of 27 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. It reaches IP20 degree of protection which is very high. It reaches IK01 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. Being made of ASA + PC material, this socket-outlet is quite reliable and resistant. It obtained 60058890B, FR.ME63.B02375 AC certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.

Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P

outlet standard - European

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - Clip-in  
Colour tint - Beige (RAL 1013)  
Connections - terminals - Screw terminals  
Cable cross section - 0.4 mm<sup>2</sup> cable(s), 2 - cable stiffness: flexible  
0.4 mm<sup>2</sup> - cable stiffness: rigid  
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6  
Electrical durability - 10000 cycles, cos phi = 0.8  
Insulation resistance - > 5 MOhm at 500 V  
Dielectric strength - 2000 V  
Material - PC: mechanism cover  
PC (polycarbonate) GF10 FR: casing  
Surface finish - Glossy  
Quantity per set - Set of 1 flow-pack  
Standards - IEC 60884-1  
DIN VDE 0620-1  
Product certifications - EAC  
VDE  
Embedding depth - 27 mm  
Depth - 37 mm  
Width - 45 mm  
Height - 45 mm  
Net weight - 0.0287 kg  
Surface treatment - Untreated  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
Ambient air temperature for operation - -5 to 35 A°C  
Ambient air temperature for storage - -5 to 50 A°C  
IK degree of protection - IK01  
IP degree of protection - IP4X  
Environmental characteristic - UV resistant  
Acetone  
Liquid soap  
Oil  
Window-cleaning fluid  
Petrol  
Alcohol  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 4 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 29 g  
Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10  
Package 2 Height - 8.2 cm  
Package 2 Width - 17.8 cm  
Package 2 Length - 24.8 cm  
Package 2 Weight - 391.3 g  
Unit Type of Package 3 - S03  
Number of Units in Package 3 - 60  
Package 3 Height - 30 cm  
Package 3 Width - 30 cm  
Package 3 Length - 40 cm  
Package 3 Weight - 2.789 kg  
Pret: 12,78 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/european-priza-new-unica-2p-10-a-2-module-bej-318899>