



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, SCHUKO, OBTURATSAU, TERMINAL FARA SURUBURI, LUCIOS, ANTIBACTERIAN, ALB**

Main

Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Mechanism

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - White (RAL 9003)

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm<sup>2</sup> cable(s), 2 - cable stiffness: flexible

0.5-2.5 mm<sup>2</sup> cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V  
Material - PC: mechanism cover  
PC (polycarbonate) GF10 FR: casing  
Surface finish - Glossy  
Quantity per set - Set of 1 flow-pack  
Standards - IEC 60884-1  
UNE 20315-1-1  
UNE 20315-1-2  
Product certifications - AENOR  
EAC  
Embedding depth - 30 mm  
Depth - 40 mm  
Width - 45 mm  
Height - 45 mm  
Net weight - 0.033 kg  
Surface treatment - Antibacterial  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
Ambient air temperature for operation - -5a€|35 A°C  
Ambient air temperature for storage - -5a€|50 A°C  
IK degree of protection - IK01  
IP degree of protection - IP21D  
Environmental characteristic - Acetone  
Bleach  
UV resistant  
Petrol  
Oil  
Alcohol  
Window-cleaning fluid  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 4.2 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 31.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8.2 cm  
Package 2 Width - 17.8 cm  
Package 2 Length - 24.8 cm  
Package 2 Weight - 411.3 g  
Unit Type of Package 3 - S04

Number of Units in Package 3 - 140

Package 3 Height - 30.0 cm

Package 3 Width - 40.0 cm

Package 3 Length - 60.0 cm

Package 3 Weight - 6.461 kg

Pret: 17,62 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-new-unica-mecanism-2p-e-16a-schuko-obturatsau-terminal-fara-suruburi-lucios-antibacterian-alb-318942>