



**SCHNEIDER PRIZA DUBLA, NEW UNICA, MECANISM, 2P E, 16A, SCHUKO, CU
OBTURATSAU, SCREW TERMINAL, LUCIOS, ANTIBACTERIAN, ALB**

Main

Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Mechanism

Socket number - 2

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 4 modules

Fixing mode - Clip-in

Colour tint - White (RAL 9003)

Connections - terminals - IPT (Isolates Piercing Terminal)

Screw terminal

Cable cross section - 0.5-2.5 mm² cable(s), 2 - cable stiffness: flexible

0.5-2.5 mm² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
Surface finish - Glossy
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
UNE 20315-1-1
UNE 20315-1-2
Product certifications - AENOR
Embedding depth - 31.1 mm
Depth - 40.4 mm
Width - 45 mm
Height - 90 mm
Net weight - 0.077 kg
Surface treatment - Antibacterial
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5a€|35 A°C
Ambient air temperature for storage - -5a€|50 A°C
IK degree of protection - IK01
IP degree of protection - IP21D
Environmental characteristic - Acetone
Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.5 cm
Package 1 Width - 4.5 cm
Package 1 Length - 9 cm
Package 1 Weight - 79 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 7.5 cm
Package 2 Width - 21.5 cm
Package 2 Length - 27 cm
Package 2 Weight - 935 g
Unit Type of Package 3 - S04

Number of Units in Package 3 - 90

Package 3 Height - 30 cm

Package 3 Width - 40 cm

Package 3 Length - 60 cm

Package 3 Weight - 9.118 kg

Pret: 56,19 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-dubla-new-unica-mecanism-2p-e-16a-schuko-cu-obturatsau-screw-terminal-lucios-antibacterian-alb-318943>