



SCHNEIDER GERMAN PRIZA, NEW UNICA, IP44, BEJ

Schneider Electric New Unica socket-outlet NU508244 is a in color beige. And this device is German standard. Its matching mounting box can be recessed into the surface of the wall with flush type. With IP44 level reached, the device has better performance against solid particle and liquid. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - 4 fixing points

Colour tint - Beige (RAL 1013)

Connections - terminals - Screwless terminals

Cable cross section - 0a€\2.5 mmA² cable(s), 2 - cable stiffness: flexible

0a€\2.5 mmA² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, $\cos \phi = 0.6$

Electrical durability - 10000 cycles, $\cos \phi = 0.8$

Insulation resistance - $> 5 \text{ M}\Omega$ at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

Surface finish - Glossy

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

UNE 20315-1-1

UNE 20315-1-2

Product certifications - AENOR

EAC

Embedding depth - 30 mm

Depth - 48 mm

Width - 74.5 mm

Height - 74.5 mm

Net weight - 0.0712 kg

Surface treatment - Untreated

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - $-5 \text{ a } 35 \text{ A}^\circ\text{C}$

Ambient air temperature for storage - $-5 \text{ a } 50 \text{ A}^\circ\text{C}$

IK degree of protection - IK01

IP degree of protection - IP44

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

Oil

Alcohol

Window-cleaning fluid

Liquid soap

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 4.8 cm

Package 1 Width - 7.5 cm

Package 1 Length - 7.5 cm

Package 1 Weight - 71.2 g

Unit Type of Package 2 - S02

Number of Units in Package 2 - 10

Package 2 Height - 15.0 cm

Package 2 Width - 30.0 cm

Package 2 Length - 40.0 cm

Package 2 Weight - 1027.0 g
Unit Type of Package 3 - P06
Number of Units in Package 3 - 160
Package 3 Height - 77.0 cm
Package 3 Width - 60.0 cm
Package 3 Length - 80.0 cm
Package 3 Weight - 26.612 kg
Pret: 41,44 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/german-priza-new-unica-ip44-bej-318959>