



### **SCHNEIDER INTRERUPATOR, NEW UNICA, MECANISM, 2-POLE 1-WAY, 16AX, 2 MODULE, SCREW TERMINALS, VOPSIT, IP4X, ALUMINIU**

Schneider Electric New Unica switch NU326230S is a mechanism in color aluminium. This is a 2-pole 1-way switch. The fixing mode of this device is clip-in. Its rated current is 16AX. It is 45 mm in width, It is 45 mm in height, and 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. Its connection terminals are screw terminals. This switch is AENOR, CE, EAC, NF certified. Being environmentally friendly, this switch is a green premium product. It is mercury free, as well as heavy metal free, taking care of the environment and your health. Besides, there is a 0 - 1 marking on the surface. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism

Technology type - Electromechanical

Switch function - 2-pole 1-way

Number of rocker - 1

Device application - Light control

Colour tint - Aluminium

Type of packing - Flow-pack

Complementary

Rated current - 16 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles,  $\cos \phi = 0.6$

Insulation resistance -  $> 5 \text{ MOhm}$  at 500 V

Dielectric strength - 2000 V  
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un,  $\cos \phi = 0.3$   
Opening distance - > 3 mm  
Actuator - Rocker  
Number of modules - 2 modules  
Pilot light - LED, colour: red, current consumption: 1.5 mA  
Connections - terminals - Screw terminals  
Cable cross section - 0.4 mm<sup>2</sup> rigid cable  
0.4 mm<sup>2</sup> flexible cable  
Material - CuZn5 Ag: terminals  
Thermoplastic ABS-UV stabilised: mechanism rocker  
PC (polycarbonate) GF10 FR: casing  
Marking - 0 - 1  
Surface finish - Glossy  
specific treatment - integrated within the material - Painted  
Fixing mode - Clip-in  
Width - 45 mm  
Height - 45 mm  
Depth - 37.75 mm  
Embedding depth - 24.65 mm  
Net weight - 0.0248 kg  
Ambient air temperature for operation - -5 to 40 A°C  
Ambient air temperature for storage - -5 to 50 A°C  
Standards - IEC 60669-1  
LV directive  
Product certifications - CE  
AENOR  
EAC  
NF  
VDE  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Oil  
UV resistant  
Acetone  
Liquid soap  
Window-cleaning fluid  
Petrol  
Alcohol  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1

Package 1 Height - 3.8 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 26.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8.0 cm  
Package 2 Width - 18.0 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 350.0 g  
Unit Type of Package 3 - S02  
Number of Units in Package 3 - 20  
Package 3 Height - 15.0 cm  
Package 3 Width - 30.0 cm  
Package 3 Length - 40.0 cm  
Package 3 Weight - 1.015 kg  
Pret: 47,83 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-mecanism-2-pole-1-way-16ax-2-module-screw-terminals-vopsit-ip4x-aluminiu-319013>