



### **SCHNEIDER BUTON CU REVENIRE, NEW UNICA, LOCATION LAMP, 10 A, 2 MODULE, BEJ**

Schneider Electric New Unica switch NU320644N is a mechanism in color beige. This is a push-button location lamp switch. Clip-in this push-button switch for the fixation. Its rated current is 10A. It is 45 mm in width, It is 45 mm in height, 34 mm in depth with an embedding depth of 22 mm. The IP rating of this device is IP20. Its connection terminals are screwless terminals. The switch is made of ASA + PC, making it as resistant as possible. Besides, there is a OFF marking on the surface. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Push-button

device presentation - Mechanism

Technology type - Electromechanical

Number of rocker - 1

Device application - Light control

Provided equipment - LED

Colour tint - Beige (RAL 1013)

Type of packing - Flow-pack

Complementary

Rated current - 10 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 40000 cycles,  $\cos \phi = 0.6$

20000 cycles,  $\cos \phi = 0.6$

Insulation resistance -  $> 5 \text{ MOhm}$  at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un,  $\cos \phi = 0.3$   
Condition of use - Indoor  
Opening distance - > 3 mm  
Actuator - Rocker  
Number of modules - 2 modules  
Pilot light - LED, colour: blue, current consumption: 0.15 mA, temperature rise: 15 A°C  
LED, colour: white, current consumption: 0.05 mA, temperature rise: 15 A°C  
Connections - terminals - Screwless terminals  
Cable cross section - 0.5 mm<sup>2</sup> rigid cable  
0.5 mm<sup>2</sup> flexible cable  
Material - ASA + PC: mechanism cover  
ABS (acrylonitrile butadiene-styrene): mechanism cover  
Marking - OFF  
Surface finish - Glossy  
specific treatment - integrated within the material - Untreated  
Fixing mode - Clip-in  
Width - 45 mm  
Height - 45 mm  
Depth - 34.25 mm  
Embedding depth - 21.15 mm  
Net weight - 0.0226 kg  
Ambient air temperature for operation - -5 to 40 A°C  
Ambient air temperature for storage - -5 to 50 A°C  
Standards - EN 60669-1  
LV directive  
EMC directive  
Product certifications - CE  
AENOR  
EAC  
NF  
VDE  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Acetone  
Bleach  
Petrol  
Window-cleaning fluid  
Liquid soap  
Oil  
UV resistant  
Alcohol  
Packing Units  
Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1  
Package 1 Height - 3.5 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 21.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8.0 cm  
Package 2 Width - 18.5 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 298.0 g  
Unit Type of Package 3 - S02  
Number of Units in Package 3 - 20  
Package 3 Height - 15.0 cm  
Package 3 Width - 30.0 cm  
Package 3 Length - 40.0 cm  
Package 3 Weight - 911.0 g  
Pret: 34,58 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/buton-cu-revenire-new-unica-location-lamp-10-a-2-module-bej-319120>