



**SCHNEIDER INTREERUPATOR, NEW UNICA, INTERMEDIATE, 10AX, 2 MODULE,
TERMINAL FARA SURUBURI, ANTIBACTERIAN, IP4X, ALB**

Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism

Technology type - Electromechanical

Switch function - Intermediate

Number of rocker - 1

Device application - Light control

Colour tint - White (RAL 9003)

Type of packing - Flow-pack

Complementary

Rated current - 10 A

10 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles, $\cos \phi = 0.6$

Insulation resistance - $> 5 \text{ MOhm}$ at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, $\cos \phi = 0.3$

Condition of use - Indoor

Opening distance - $> 3 \text{ mm}$

Actuator - Rocker

Number of modules - 2 modules

Connections - terminals - Screwless terminals

Cable cross section - 0.25 mm^2
Marking - Without marking
Surface finish - Glossy
specific treatment - integrated within the material - Antibacterial
Fixing mode - Clip-in
Width - 45 mm
Height - 45 mm
Depth - 34.25 mm
Embedding depth - 21.15 mm
Net weight - 0.0216 kg
Ambient air temperature for operation - $-5 \text{ to } 40 \text{ A}^\circ\text{C}$
Ambient air temperature for storage - $-5 \text{ to } 50 \text{ A}^\circ\text{C}$
Standards - EN 60669-1
LV directive
EMC directive
Product certifications - CE
AENOR
EAC
NF
VDE
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IP degree of protection - IP4X
IK degree of protection - IK04
Environmental characteristic - Alcohol
Window-cleaning fluid
Acetone
Petrol
UV resistant
Oil
Bleach
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 3.5 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 22.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 8.2 cm
Package 2 Width - 17.7 cm
Package 2 Length - 18.5 cm

Package 2 Weight - 304.0 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 200
Package 3 Height - 30.0 cm
Package 3 Width - 40.0 cm
Package 3 Length - 60.0 cm
Package 3 Weight - 6.783 kg

Pret: 38,94 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-intermediate-10ax-2-module-terminal-fara-suruburi-antibacterian-ip4x-alb-319143>