



SCHNEIDER BUTON JALUZELE, NEW UNICA, 10 AX, 250 V, AC, 1 MODULE, ALB

Schneider Electric New Unica switch NU310818SC is a mechanism in color white. This is a roller blind switch. Clip-in this rocker switch for the fixation. Its rated current is 10AX. It is 22.4 mm in width, It is 45 mm in height, and 33 mm in depth with an embedding depth of 21 mm. The IP rating of this device is IP20. Its connection terminals are screw terminals. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Control

Product or component type - Shutter control

device presentation - Mechanism

Rated current - 10 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Fixing mode - Clip-in

Colour tint - White (RAL 9003)

Complementary

device mounting - Flush

Number of modules - 1 module

Technology type - Electromechanical

Actuator - Rocker

Number of rocker - 2

Switch function - 1-pole 2-way

Switch application - Roller blind

Number of poles - 1

Contacts type and composition - 1 C/O

mechanical interlocking - Interlock between up/down

[I_u] rated interrupted current - 2.5 A for motor

Opening distance - > 3 mm

Pilot light - Without LED

Marking - Down

UP

Connections - terminals - Screw terminals

Cable cross section - 2.5 mm² flexible cable

1.5-2.5 mm² flexible cable

2.5 mm² rigid cable

1.5-2.5 mm² rigid cable

Minimum load breaking capacity - 200 operations 1.25 I_n and 1.1 U_n, cos phi = 0.3

Electrical durability - 10000 cycles, cos phi = 0.6

Insulation resistance - > 5 MΩ at 500 V

Dielectric strength - 2000 V

Material - ASA + PC: mechanism cover

ABS (acrylonitrile butadiene-styrene): mechanism cover

Standards - LV directive

EMC directive

EN 60669-1

Product certifications - ISI

CE

Ambient air temperature for operation - -5-40 A°C

Ambient air temperature for storage - -5-40 A°C

Embedding depth - 31.5 mm

Depth - 40.6 mm

Width - 22.5 mm

Height - 45 mm

Net weight - 0.036 kg

Environment

IK degree of protection - IK04

IP degree of protection - IP4X

Environmental characteristic - Window-cleaning fluid

Liquid soap

Acetone

UV resistant

Oil

Bleach

Petrol

Alcohol

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 4.05 cm

Package 1 Width - 2.25 cm

Package 1 Length - 4.5 cm

Package 1 Weight - 21 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10

Package 2 Height - 6.5 cm

Package 2 Width - 12 cm

Package 2 Length - 18.5 cm

Package 2 Weight - 278.3 g

Unit Type of Package 3 - S04

Number of Units in Package 3 - 360

Package 3 Height - 30 cm

Package 3 Width - 40 cm

Package 3 Length - 60 cm

Package 3 Weight - 10.722 kg

Pret: 35,29 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/buton-jaluzele-new-unica-10-ax-250-v-ac-1-module-alb-319153>