



SCHNEIDER BUTON JALUZELE, NEW UNICA, 10 A, 250 V, AC, 1 MODULE, 2 POLES, ALB

Schneider Electric New Unica switch NU310918SC is a mechanism in color white. This is a double 2-way roller blind switch. Clip-in this rocker switch for the fixation. Its rated current is 10A. It is 22.4 mm in width, 45 mm in height 33 mm in depth with an embedding depth of 21 mm. The IP rating of this device is IP20. Its connection terminals are screw terminals. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.Main

Range - New Unica

Device application - Control

Product or component type - Shutter control

device presentation - Mechanism

Rated current - 10 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Fixing mode - Clip-in

Colour tint - White (RAL 9003)

Complementary

device mounting - Flush

Number of modules - 1 module

Technology type - Electromechanical

Actuator - Rocker

Number of rocker - 2

Switch function - 2-pole 2-way

Switch application - Roller blind

Number of poles - 2

Contacts type and composition - 1 C/O + 1 C/O
mechanical interlocking - Interlock between up/down
[Iu] rated interrupted current - 2.5 A for motor
Opening distance - > 3 mm
Pilot light - Without LED
Marking - UP
Down
Connections - terminals - Screw terminals
Cable cross section - 2.5 mm² flexible cable
1.5-2.5 mm² flexible cable
2.5 mm² rigid cable
1.5-2.5 mm² rigid cable
Minimum load breaking capacity - 200 operations 1.25 I_n and 1.1 U_n, cos phi = 0.3
Electrical durability - 10000 cycles, cos phi = 0.6
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - ASA + PC: mechanism cover
ABS (acrylonitrile butadiene-styrene): mechanism cover
Standards - LV directive
EN 60669-1
EMC directive
Product certifications - ISI
CE
Ambient air temperature for operation - -5-40 A°C
Ambient air temperature for storage - -5-40 A°C
Embedding depth - 31.5 mm
Depth - 40.6 mm
Width - 22.5 mm
Height - 45 mm
Net weight - 0.0382 kg
Environment
IK degree of protection - IK04
IP degree of protection - IP4X
Environmental characteristic - Window-cleaning fluid
Petrol
Alcohol
UV resistant
Bleach
Oil
Liquid soap
Acetone
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.05 cm
Package 1 Width - 2.25 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 41 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 6.5 cm
Package 2 Width - 12 cm
Package 2 Length - 18.5 cm
Package 2 Weight - 478.3 g

Unit Type of Package 3 - S03
Number of Units in Package 3 - 160
Package 3 Height - 30 cm
Package 3 Width - 30 cm
Package 3 Length - 40 cm
Package 3 Weight - 8.094 kg
Pret: 44,97 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/buton-jaluzele-new-unica-10-a-250-v-ac-1-module-2-poles-alb-319156>