



**SCHNEIDER BUTON JALUZELE, NEW UNICA, 10 A, 250 V, AC, 1 MODULE, 2 POLES, BEJ**

Schneider Electric New Unica switch NU310944SC is a mechanism in color beige. This is a double 2-way roller blind switch. The device's fixing mode is clip-in. Its rated current is 10A. It is 22.4 mm in width, It is 45 mm in height, and 33 mm in depth with an embedding depth of 21 mm. It reaches IP20 degree of protection which is very high. This switch has screw terminals connection terminals. The switch is made of ASA + PC, making it resistant and durable. Besides, there is a UP, down marking on the surface. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Control

Product or component type - Shutter control

device presentation - Mechanism

Rated current - 10 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Fixing mode - Clip-in

Colour tint - Beige (RAL 1013)

Complementary

device mounting - Flush

Number of modules - 1 module

Technology type - Electromechanical

Actuator - Rocker

Number of rocker - 2

Switch function - 2-pole 2-way

Switch application - Roller blind

Number of poles - 2

Contacts type and composition - 1 C/O + 1 C/O

mechanical interlocking - Interlock between up/down

[I<sub>u</sub>] rated interrupted current - 2.5 A for motor

Opening distance - > 3 mm

Pilot light - Without LED

Marking - Down

UP

Connections - terminals - Screw terminals

Cable cross section - 2.5 mm<sup>2</sup> flexible cable

1.5-2.5 mm<sup>2</sup> flexible cable

2.5 mm<sup>2</sup> rigid cable

1.5-2.5 mm<sup>2</sup> rigid cable

Minimum load breaking capacity - 200 operations 1.25 I<sub>n</sub> and 1.1 U<sub>n</sub>, cos phi = 0.3

Electrical durability - 10000 cycles, cos phi = 0.6

Insulation resistance - > 5 MΩ at 500 V

Dielectric strength - 2000 V

Material - ASA + PC: mechanism cover

ABS (acrylonitrile butadiene-styrene): mechanism cover

Standards - EN 60669-1

EMC directive

LV directive

Product certifications - ISI

CE

Ambient air temperature for operation - -5-40 A°C

Ambient air temperature for storage - -5-40 A°C

Embedding depth - 31.5 mm

Depth - 40.6 mm

Width - 22.5 mm

Height - 45 mm

Net weight - 0.0382 kg

Environment

IK degree of protection - IK04

IP degree of protection - IP4X

Environmental characteristic - Window-cleaning fluid

Petrol

Alcohol

UV resistant

Oil

Bleach

Liquid soap

Acetone

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 4.05 cm

Package 1 Width - 2.25 cm

Package 1 Length - 4.5 cm

Package 1 Weight - 41 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10

Package 2 Height - 6.5 cm

Package 2 Width - 12 cm

Package 2 Length - 18.5 cm

Package 2 Weight - 478.3 g  
Unit Type of Package 3 - S03  
Number of Units in Package 3 - 160  
Package 3 Height - 30 cm  
Package 3 Width - 30 cm  
Package 3 Length - 40 cm  
Package 3 Weight - 8.094 kg  
Pret: 44,97 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/buton-jaluzele-new-unica-10-a-250-v-ac-1-module-2-poles-bej-319160>