



SCHNEIDER VARIATOR, NEW UNICA, ROTARY PUSH TYPE, ANTRACIT

Schneider Electric New Unica dimmer NU351454 is a mechanism in color anthracite with 2 modules. 230V is the rated operational voltage. And the dimmer's associated fuse rating is 16. And the control type of this dimmer is local control, remote control by auxiliary push-button. Its protection type is automatic overload protection, overheating protection, short-circuit protection, taking care of your safety as much as possible. Its matching mounting box can be recessed into the surface of the wall with flush type. Its connection terminals are screw terminal. What's more, its directives are 2014/30/EU - electromagnetic compatibility, 2014/35/EU - low voltage directive. It is 45 mm in width, 45 mm in height, 47 mm in depth, and with an embedding depth of 29 mm. And the product weighs 0.129 kg. The IP rating of this device is IP20, IP21. It obtained CE, EAC, FIMKO, NEMKO, NF, SEMKO, VDE certificate as well. What's more, it well satisfied the standard of EN 300-328, EN 301-489-17, EN 60669-2-1, EN 60730-2-7. And it is mercury free Being environmentally friendly, this dimmer is a green premium product too. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Product brand - Schneider Electric

Range - New Unica

Type number - NH3514

Product or component type - Dimmer

Complementary

device presentation - Mechanism

Device application - Light control

Dimmer type - Universal

Dimmer control - Rotary push type

Load type - Incandescent lamp: 5...200 W at 230 V AC

Halogen lamp: 5...150 W at 230 V AC

LED lamp: 5...100 VA at 230 V AC (RC LED mode)

LED lamp: 5...20 VA at 230 V AC (RL LED mode)

LV halogen lamps: 5...150 VA at 12 V AC (electronic transformer)
LV halogen lamps: 5...150 VA at 12 V AC (wound transformer)
Function available - With memory function
[Ue] rated operational voltage - 230 V AC 50 Hz
Associated fuse rating - 16 A
Protection type - Short-circuit protection
Automatic overload protection
Overheating protection
colour - Anthracite (RAL 7021)
Surface finish - Painted powder coated
Number of modules - 2 modules
Number of outputs - 1
Control type - Local control dimming up/down control
Local control automatic load detection
Remote control by auxiliary push-button
Connected auxiliaries - Unlimited number of push-buttons, distance : 50 m
Provided equipment - User manual
Connections - terminals - Screw terminal
Number of loop terminals - 2
Clamping connection capacity - 1.5...2.5 mm² for solid cable(s)
1.5...2.5 mm² for solid stranded cable(s)
Shape of screw head - Pozidriv No 1 and combi
Tightening torque - 0.5 N.m
Material - PC (polycarbonate) GF10 FR: casing
Metal: terminals
Thermoplastic ABS-UV stabilised: central plate
device mounting - Flush
Fixing mode - By screws
Type of installation - Indoor installation
Quantity per set - 1 carton
Embedding depth - 29 mm
Depth - 47 mm
Width - 45 mm
Height - 45 mm
Net weight - 0.129 kg
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - 5a€140 A°C
Ambient air temperature for storage - 5a€140 A°C
IP degree of protection - IP20
IP21 with marking on visual parts
IK degree of protection - IK04
Environmental characteristic - Alcohol
Petrol
UV resistant

Oil
Acetone
Liquid soap
Bleach
Window-cleaning fluid
Standards - EN 60669-2-1
EN 60730-2-7
EN 301-489-17
EN 300-328
Directives - 2014/35/EU - low voltage directive
2014/30/EU - electromagnetic compatibility
Product certifications - EAC
SEMKO
FIMKO
VDE
NF
CE
NEMKO
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.7 cm
Package 1 Width - 9.5 cm
Package 1 Length - 9.5 cm
Package 1 Weight - 111.0 g
Unit Type of Package 2 - S01
Number of Units in Package 2 - 4
Package 2 Height - 15.0 cm
Package 2 Width - 15.0 cm
Package 2 Length - 40.0 cm
Package 2 Weight - 652.0 g
Pret: 545,34 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/variator-new-unica-rotary-push-type-antracit-319201>