



## SCHNEIDER NEW UNICA - STATIE DE LUCRU - INCASTRAT - 2 X 4 MODULE - ALUMINIU

Schneider Electric New Unica workstation NU172430 is in color aluminium. It is 165 mm in width, 165 mm in height, 62 mm in depth. And the product weighs 0.278 kg. With 2 x 4 modules. Its fixing mode is claws, embedment. Its matching mounting box can be recessed into the surface of the wall with flush type. The workstation is made of ABS (acrylonitrile butadiene-styrene), PC, making it as resistant as possible. Besides, it reaches IK04 protection level, which can help protect against impact. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This workstation is SVHC (substances of very high concern) free too. This device is (compatible with) Unica. Besides it is halogen free halogen free, which is good for your health. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Workstation

Number of modules - 2 x 4 modules

Fixing mode - Embedment

Claws

Colour tint - Aluminium

Complementary

Provided equipment - Cover frame

Fixing frame

device mounting - Flush

Cable entry - 5 knock-outs 20 mm for diameter

5 knock-outs 25 mm for diameter

2 bottom cable entries 50 x 35 mm for size 20 mm for diameter

2 bottom cable entries 50 x 35 mm for size 25 mm for diameter

Fire resistance - 850 A°C, extinction time <30 s

Material - ABS (acrylonitrile butadiene-styrene): separator

PC: box

ABS (acrylonitrile butadiene-styrene): cover frame

Depth - 62 mm

Width - 165 mm

Height - 165 mm

Net weight - 0.278 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 8.2 cm

Package 1 Width - 18.5 cm

Package 1 Length - 18.5 cm

Package 1 Weight - 380.0 g

Unit Type of Package 2 - S04

Number of Units in Package 2 - 20

Package 2 Height - 30.0 cm

Package 2 Width - 40.0 cm

Package 2 Length - 60.0 cm

Package 2 Weight - 8.365 kg

Pret: 115,14 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-statie-de-lucru-incastrat-2-x-4-module-aluminiu-319726>