



SCHNEIDER NEW UNICA - STATIE DE LUCRU - INCASTRAT - 4 X 4 MODULE - ALB

Schneider Electric New Unica workstation NU174418 is in color white. It is 300 mm in width, 165 mm in height, 62 mm in depth. And the product weighs 0.514 kg. With 4 x 4 modules. The device's fixing mode is claws, embedment. Its matching mounting box can be recessed into the surface of the wall with flush type. Being made of ABS (acrylonitrile butadiene-styrene), PC material, this workstation is quite reliable and resistant. Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This workstation is SVHC (substances of very high concern) free too. This device is (compatible with) Unica. Besides it is halogen free halogen free, which is good for your health. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Workstation

Number of modules - 4 x 4 modules

Fixing mode - Embedment

Claws

Colour tint - White (RAL 9003)

Complementary

Provided equipment - Cover frame

Fixing frame

device mounting - Flush

Cable entry - 4 bottom cable entries 50 x 35 mm for size 25 mm for diameter

8 knock-outs 20 mm for diameter

8 knock-outs 25 mm for diameter

4 bottom cable entries 50 x 35 mm for size 20 mm for diameter

Fire resistance - 850 A°C, extinction time <30 s

Material - ABS (acrylonitrile butadiene-styrene): separator

PC: box
ABS (acrylonitrile butadiene-styrene): cover frame
Depth - 62 mm
Width - 300 mm
Height - 165 mm
Net weight - 0.514 kg
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IK degree of protection - IK04
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 8.0 cm
Package 1 Width - 18.5 cm
Package 1 Length - 31.5 cm
Package 1 Weight - 656.0 g
Unit Type of Package 2 - S04
Number of Units in Package 2 - 10
Package 2 Height - 30.0 cm
Package 2 Width - 40.0 cm
Package 2 Length - 60.0 cm
Package 2 Weight - 7.302 kg
Unit Type of Package 3 - P06
Number of Units in Package 3 - 40
Package 3 Height - 77.0 cm
Package 3 Width - 80.0 cm
Package 3 Length - 60.0 cm
Package 3 Weight - 37.708 kg
Pret: 116,33 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-statie-de-lucru-incastrat-4-x-4-module-alb-319731>