



**SCHNEIDER NEW UNICA - STATIE DE LUCRU - INCASTRAT - 2 X 8 MODULE -
ANTIBACTERIAN - ALUMINIU**

Main

Range - New Unica

Product or component type - Workstation

Number of modules - 2 x 8 modules

Fixing mode - Embedment

Claws

Colour tint - Aluminium

Complementary

Provided equipment - Cover frame

Fixing frame

device mounting - Flush

Cable entry - 6 knock-outs 20 mm for diameter

6 knock-outs 25 mm for diameter

2 bottom cable entries 45 x 25 mm for size 20 mm for diameter

4 bottom cable entries 50 x 35 mm for size 25 mm for diameter

Fire resistance - 850 A°C, extinction time Material - ABS (acrylonitrile butadiene-styrene): separator

PC: box

ABS (acrylonitrile butadiene-styrene): cover frame

PC: tower

Surface treatment - Antibacterial

Depth - 62 mm

Width - 230 mm

Height - 165 mm

Net weight - 0.468 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IK degree of protection - IK04
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 8.000 cm
Package 1 Width - 18.000 cm
Package 1 Length - 25.000 cm
Package 1 Weight - 608.000 g
Unit Type of Package 2 - S04
Number of Units in Package 2 - 14
Package 2 Height - 30.000 cm
Package 2 Width - 40.000 cm
Package 2 Length - 60.000 cm
Package 2 Weight - 9.277 kg
Unit Type of Package 3 - P06
Number of Units in Package 3 - 56
Package 3 Height - 75.000 cm
Package 3 Width - 60.000 cm
Package 3 Length - 80.000 cm
Package 3 Weight - 44.500 kg

Pret: 177,78 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-statie-de-lucru-incastrat-2-x-8-module-antibacterian-aluminiu-319740>