



SOLENTIS PANEL VOLTA WHITE LED 30W 4000K 295X595 MM ALB

Accesorii da

Culoare carcasa alb

Curent iesire driver (A) 0.75

Curent nominal (A) 0.19

Dimensiuni (mm) 295x595

Distorsiuni armonice THD (%) 16.3

Durata de viata (ore) 40000

Eficienta (lm/W) 100

Factor de protectie (IP) IP40

Factor de putere (cos ϕ) 0.98

Flux luminos (lm) 3040

Frecventa nominala (Hz) 50-60

Indicele de redare a culorii (CRI) 80

Masa echipament (kg) 1.9

Material carcasa aluminiu

Material dispersor policarbonat

Montaj suspendat/aplicat

Protectie la scurtcircuit da

Protectie suprasarcina da

Putere (W) 30

Temperatura de culoare (K) 4000

Temperatura mediului ambiant (grade C) -20...+40

Tensiune iesire driver (V) 25-42

Tensiune nominala (V) 180-260

Tip sursa luminoasa SMD LED 2835

Toleranta fluxului luminos 5

Umiditatea mediului ambiant (%) 60

Unghi de dispersie (grd) 115
Pret: 117,53 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/panel-volta-white-led-30w-4000k-295x595-mm-alb-335717>