



**PHILIPS CORP ILUMINAT STRADAL PHILIPS BGP307 LED69-4S/740 6900LM II DM50
48/60A CLEARWAY2**

Caracteristici generale

Tip de sursa: LED neinlocuibil

Echipat cu sursa: Da

Grad de protectie (IP): IP66

Clasa de protectie la impact: IK08

Caracteristici materiale

Material carcasa: Aluminiu

Culoare carcasa: Aluminiu

Material dispersor/ abajur: Sticla transparenta

Caracteristici tehnice iluminat

Indice de redare a culorilor (CRI): 70-79

Temperatura de culoare: 4000 K

Flux luminos nominal conform IEC 62722-2-1: 6900 lm

Durata estimata de viata L70/B50 la 25 °C: 0 h

Durata estimata de viata L80/B10 la 25 °C: 0 h

Durata estimata de viata L90/B10 la 25 °C: 0 h

Eficienta corp de iluminat: 0 Lm/W

Caracteristici electrice

Putere sistem: 0 W

Tensiune alimentare: 220-240 V

Clasa de protectie la atingere: II

Cu cablu electric: Nu

Caracteristici montaj

Modalitate de montare: Suport vertical/orizantal

Pret: 1.596,03 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-iluminat-stradal-philips-bgp307-led69-4s-740-6900lm-ii-dm50-48-60a-clearway2-343637>