



ULTRALUX SENZOR CU MICROUNDRE, DIMMABIL 0-10V DC, IP65

Tensiune de alimentare: 220V-240V AC, 50-60Hz Unghi de detectie: 360° Distanța de detectie: 5m (50%)/ 10m (100%) (adjustabil) Senzor de lumina: 2 lx, 10 lx, 50 lx, 2000 lx (adjustabil) HF banda: 5.8 GHz CW radar/ISM band Puterea de transmisie < 0.2 mW Puterea consumata: approx 0.9 W Timer: 5s/ 30s/ 90s/ 3min/ 5min/ 10min/ 20min/ 30min (adjustabil) Viteza de detectie la miscare: 0.6 - 1.5 m/s Inaltime instalare: 4-15 m Stand-by period: 10 s/ 1min/ 5min/ 10min/ 30min/ 60min/ + ?/ 0 s (adjustabil) Incarcarea maxima: 800 W (resistive load) Stand-by DIM level: 10%, 20%, 30%, 50% (adjustable) Metoddata de dimare: 1-10V DC IP: IP65 Garantie: 3 years Grad de protectie IP IP65

Tip Detectie MICROUNDRE

Gama Detectare 360°

Alimentare 220-240V AC, 50-60Hz

Puterea maxima 800W

Distanța detectare 5m (50%)/ 10m (100%) (reglabil)

Inaltime de instalare 4-15 m

Lumina ambientală

Indice de protectie IP65 (rezistent la apa)

Consum 0.9W

Dimensiuni 71,6x55 mm

Garantie 3 Ani

Pret: 229,46 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/senzor-cu-microundre-dimmabil-0-10v-dc-ip65-360715>