



SCHRACK INTRERUPATOR GENERAL 4P 50-63A 50 KA SCHRACK

EAN-Code	9004840892741
L?ime net?	120,00mm
În?ime	140,00mm
Mas? net?	1,55kg.
disipare	26,80W
Temperatura minim? a mediului ambiant	-40°C
Temperatura maxim? a mediului ambiant	70°C
Echipament	Înteruptor compact
Standard	EN 60947-2
Curent nominal	63A
Tensiune nominal?	< 690VAC
Short circuit switching capacity (400V)	50kA
M?rime	1
Declan?ator	Thermomagnetic release - Type A
Poli	4
Grad de poluare	3
Grad de protec?ie	IP40
Tensiune nominal? de izola?ie (U _i)	1000V
Tinere la impuls de tensiune [U _{imp}]	8000V
Rated ultimate short-circuit breaking capacity I _{cu}	50kA
Rated service breaking capacity I _{cs}	50kA

AC 380/400/415V	50kA (Icu) / 50kA (Ics)
AC 440V	50kA (Icu) / 50kA (Ics)
AC 500V	40kA (Icu) / 40kA (Ics)
AC 660/690V	8kA (Icu) / 8kA (Ics)
Durat? de via?? (Cicluri de operare)	##
AC 415V, In	8000
AC 690V, In	2000

Pret: 740,50 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-4p-50-63a-50-ka-schrack>