



### **BTICINO L.NOW - LAMPA DE LECTURA+DEV. 230 V C.A.**

Descoper? L.NOW - Lamp? de lectur?+dev. 230 V c.a. din categoria Prize, Intreruptoare & Doze - Doza modulara, un produs cu codul KW4362. Acesta ofer? caracteristici excelente: Suitable for wall mounting Yes

Suitable for suspended mounting No

Suitable for ceiling mounting No

Suitable for built-in mounting Yes

Suitable for surface mounting Yes

Suitable for light line configuration No

Suitable for workplace according to EN 12464-1 No

Lamp type LED not exchangeable

With light source Yes

Suitable for number of light sources 1

Lamp holder Other

Housing material Plastic

Surface protection housing Untreated

Housing colour Black

Material cover Plastic, opal

Type of grid White

Voltage type AC

Nominal voltage 230-250 V

Nominal current 15-25 mA

Type of control gear LED operating device voltage-controlled

With control gear No

Exchangeable control gear No

Dimming 0-10 V No

Dimming 1-10 V No

Dimming DALI-2 No

Dimming DALI No

Dimming DMX No  
Dimming DSI No  
Dimming potentiometer (integrated) No  
Dimming LineSwitch No  
Dimming manufacturer's proprietary system No  
Dimming mains voltage modulation No  
Dimming phase cut-off No  
Dimming phase cut-on No  
Dimming programmable Yes  
Dimming RF No  
Dimming Sine Wave Reduction No  
Dimming Touch and Dim Yes  
Dimming Zigbee No  
Dimming with push-button Yes  
No dim function No  
Light distributor Diffuser lens/optic/panel  
Light sharing Symmetric/asymmetric  
Beam angle Open beam/diffuse  
Light outlet Direct  
Degree of protection (IP) IP40  
Degree of impact strength (IK) IK04  
Protection class None  
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 No  
Rated ambient temperature according to IEC 62722-2-1 -5-35 °C  
Suitable for emergency lighting No  
Emergency power supply integrated No  
With movement sensor No  
With light sensor No  
Covering of the luminaire with thermally insulating material possible No  
With air slots Yes  
Filament test according to IEC 60695-2-11 None  
Suitable for lamp power 0.1-0.2 W  
Max. system power 0.3 W  
Rated luminous flux according to IEC 62722-2-1 246 lm  
Colour of light White  
Colour temperature 4000-5500 K  
Colour rendering index CRI 80-89  
Width 22 mm  
Height/depth 375 mm  
Length 86 mm  
Built-in width 22 mm  
Built-in height/depth 86 mm  
Type of wiring Ending  
Number of poles 2  
Conductor cross section 1.5 mm<sup>2</sup>  
Connection type Screwed terminal  
Operation by Bluetooth No  
Compatible with Apple HomeKit No  
Compatible with Google Assistant No  
Compatible with Amazon Alexa No  
IFTTT support available No  
Operating / setting temperature -5-35 °C  
Storage temperature -10-70 °C  
Frequency 50-60 Hz

Standby consumption 136 mA

Mandatory neutral No

RAL-number 9003

Halogen free Yes

Antimicrobial treatment No

Terminals capacity 1-1.5 mm<sup>2</sup>

Cable nature for connection Flexible or rigid

With socket outlet No

Fitted with rainproof plate protection No

With complementary luminous signal No

Supplied remote control No

Maximum Input cable diameter 2.5 mm

Vertical fixing center distance 9-9.2 mm

Horizontal fixing center distance 4-4.2 mm

Cable support Screw cable clamp

Auto switch No

Control mode Wired

Addressable No

Connected object No. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.

Pret: 566,07 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/l-now-lampa-de-lectura-dev-230-v-c-a>