



### **BTICINO MATIX - LAMPA MONTAJ INCASTRAT CU LEDURI 1 MOD**

Descoper? matix - Lamp? montaj incastat cu leduri 1 mod din categoria Prize, Intrerupatoare & Doze - Doza modulara, un produs cu codul A5781. Acesta ofer? caracteristici excelente: Suitable for wall mounting Yes

Suitable for suspended mounting No

Suitable for ceiling mounting No

Suitable for built-in mounting Yes

Suitable for surface mounting No

Suitable for light line configuration No

Suitable for workplace according to EN 12464-1 No

Lamp type LED not exchangeable

With light source Yes

Lamp holder Other

Housing material Plastic

Housing colour White

Material cover Plastic, opal

Type of grid White

Voltage type AC

Nominal voltage 230-250 V

Nominal current 15-25 mA

Type of control gear LED operating device voltage-controlled

With control gear No

Dimming 0-10 V No

Dimming 1-10 V No

Dimming DALI No

Dimming DMX No

Dimming DSI No

Dimming potentiometer (integrated) No

Dimming LineSwitch No

Dimming manufacturer's proprietary system No  
Dimming mains voltage modulation No  
Dimming phase cut-off No  
Dimming phase cut-on No  
Dimming programmable No  
Dimming RF No  
Dimming Sine Wave Reduction No  
Dimming Touch and Dim No  
Dimming Zigbee No  
Dimming with push-button No  
No dim function Yes  
Light sharing Symmetric  
Beam angle Extreme wide beam  $>80^\circ$   
Light outlet Direct  
Degree of protection (IP) IP41  
Protection class None  
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 No  
Rated ambient temperature according to IEC 62722-2-1 -5-49 °C  
Suitable for emergency lighting Yes  
With movement sensor No  
With light sensor Yes  
Covering of the luminaire with thermally insulating material possible No  
With air slots Yes  
Suitable for lamp power 0.1-0.1 W  
Max. system power 0 W  
Rated luminous flux according to IEC 62722-2-1 249 lm  
Colour of light White  
Colour temperature 4000-5500 K  
Colour rendering index CRI 80-89  
Width 23.4 mm  
Height/depth 49.2 mm  
Length 51 mm  
Built-in length 47 mm  
Built-in width 23.4 mm  
Built-in height/depth 49.2 mm  
Operating / setting temperature -5-49 °C  
Storage temperature -10-69 °C  
Frequency 50-50 Hz  
Standby consumption 139 mA  
Mandatory neutral No  
Halogen free Yes  
Antimicrobial treatment No  
Terminals capacity 1.5-2.5 mm<sup>2</sup>  
Cable nature for connection Flexible  
With socket outlet No  
Fitted with rainproof plate protection No  
With complementary luminous signal No  
Supplied remote control No  
Maximum Input cable diameter 2.5 mm  
Vertical fixing center distance 4.5-4.5 mm  
Cable support Screw cable clamp  
Control mode Wired  
Connected object No. Ideal pentru proiectele tale, asigurand eficienta si calitate superioara?  
Pret: 447,71 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/matix-lampa-montaj-incestrat-cu-leduri-1-mod>