



BTICINO LL - MAGN DIF 1P+N 10A 3KA 10MA TECH

Descoper? LL - magn dif 1P+N 10A 3kA 10mA tech din categoria Prize, Intreruptoare & Doze - Doza modulara, un produs cu codul NT4305/10. Acesta ofer? caracteristici excelente: Number of poles (total) 1
Number of protected poles 1
Rated voltage 230 V
Rated current 10 A
Rated fault current 0.01 A
Leakage current type Other
Current limiting class 1
Rated short-circuit breaking capacity according to EN 61009 3 kA
Rated short-circuit breaking capacity according to IEC 60947-2 3 kA
Rated short-circuit breaking capacity Icn according to EN 61009-1 3 kA
Frequency 50/60 Hz
Release characteristic C
Concurrently switching neutral conductor Yes
Ambient temperature during operating -5-50 °C
Built-in depth 33.5 mm
Degree of protection (IP) IP20
Connectable conductor cross section solid-core 2.5-2.5 mm²
Width 44 mm
Height 44 mm
Depth 44.5 mm
Degree of impact strength (IK) Not applicable
Storage temperature -10-70 °C
Connection type Screwed terminal. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.
Pret: 546,66 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/ll-magn-dif-1p-n-10a-3ka-10ma-tech>