



BTICINO LL - MAGN DIF 1P+N 10A 3KA 10MA TECH

Descoper? LL - magn dif 1P+N 10A 3kA 10mA tech din categoria Prize, Intreruptoare & Doze - Doza modulara, un produs cu codul NT4305/10. Acesta ofer? caracteristici excelente: Number of poles (total) 1
Number of protected poles 1

Rated voltage 230 V

Rated current 10 A

Rated fault current 0.01 A

Leakage current type Other

Current limiting class 1

Rated short-circuit breaking capacity according to EN 61009 3 kA

Rated short-circuit breaking capacity according to IEC 60947-2 3 kA

Rated short-circuit breaking capacity Icn according to EN 61009-1 3 kA

Frequency 50/60 Hz

Release characteristic C

Concurrently switching neutral conductor Yes

Ambient temperature during operating -5-50 °C

Built-in depth 33.5 mm

Degree of protection (IP) IP20

Connectable conductor cross section solid-core 2.5-2.5 mm²

Width 44 mm

Height 44 mm

Depth 44.5 mm

Degree of impact strength (IK) Not applicable

Storage temperature -10-70 °C

Connection type Screwed terminal. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.

Pret: 546,66 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/ll-magn-dif-1p-n-10a-3ka-10ma-tech>