



**BTICINO PRIZA 2P+T 16A 250VCA STD. FR. PORT-ETICHETA LIVING LIGHT -TECH -
2 MODULE**

Descoper? Priz? 2P+T 16A 250Vca Std. FR. port-eticheta Living Light -Tech - 2 module din categoria Prize, Intrerupatoare & Doze - Doza modulara, un produs cu codul NT4146. Acesta ofer? caracteristici excelente:

Model Earthing pin

Concurrently switching neutral conductor No

Protective contact Round

Number of active contacts (round) 2

Number of active contacts (flat) 0

Number of active contacts (square) 0

With complementary luminous signal No

Number of ports USB-A 0

Number of ports USB-C 0

Number of units 1

Number of modules (module system) 2

Number of socket outlets switchable 0

Number of phases 1

Imprint/indication None

Connection type Screwed terminal

With hinged lid No

With enhanced contact protection Yes

Label space/information surface No

Colour Aluminium

RAL-number (similar) 9006

Metallic colour No

Transparent No

Lockable No

Eject-mechanism No

Insulated mounting No
With function lighting No
With orientation lighting No
Over voltage protection No
Fault current protection No
With miniature fuse No
Special power supply No special power supply
Mounting method Flush-mounted
Type of fastening Snap mounting (engagement)
Material Plastic
Material quality Thermoplastic
Halogen free Yes
Surface protection Lacquered
Surface finishing Glossy
Antimicrobial treatment No
With loop through function Yes
With on/off switch No
Colour of switch operator Aluminium
Rotated central insert No
Nominal current 16 A
Nominal voltage 250 V
Frequency 50-60 Hz
Suitable for degree of protection (IP) IP20
Degree of impact strength (IK) IK00
Device width 44 mm
Device height 44 mm
Device depth 41.5 mm
Min. depth of built-in installation box 40.5 mm
Compatible with Apple HomeKit No
Compatible with Amazon Alexa No
Compatible with Google Assistant No
IFTTT support available No
With Wi-Fi signal repeater No
With built-in bluetooth speaker No
For heavy conditions according to VDE No
Built-in depth 30.5 mm
Operating / setting temperature -5-35 °C
Storage temperature -5-35 °C
Voltage type AC
Power Delivery No
Cable nature for connection Flexible or rigid
Cable section 2.5-2.5 mm²
Cable support Other
Assembly arrangement Basic element with central cover plate
Connected object No. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.
Pret: 69,69 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-2p-t-16a-250vca-std-fr-port-eticheta-living-light-tech-2-module>