



**BTICINO PRIZA 2P+T 16A 250VCA STD. FR. PORT-ETICHETA LIVING LIGHT -TECH - 2 MODULE**

Descoper? Priz? 2P+T 16A 250Vca Std. FR. port-eticheta Living Light -Tech - 2 module din categoria Prize, Intrerupatoare & Doze - Doza modulara, un produs cu codul NT4146. Acesta ofer? caracteristici excelente:

Model Earthing pin

Concurrently switching neutral conductor No

Protective contact Round

Number of active contacts (round) 2

Number of active contacts (flat) 0

Number of active contacts (square) 0

With complementary luminous signal No

Number of ports USB-A 0

Number of ports USB-C 0

Number of units 1

Number of modules (module system) 2

Number of socket outlets switchable 0

Number of phases 1

Imprint/indication None

Connection type Screwed terminal

With hinged lid No

With enhanced contact protection Yes

Label space/information surface No

Colour Aluminium

RAL-number (similar) 9006

Metallic colour No

Transparent No

Lockable No

Eject-mechanism No

Insulated mounting No  
With function lighting No  
With orientation lighting No  
Over voltage protection No  
Fault current protection No  
With miniature fuse No  
Special power supply No special power supply  
Mounting method Flush-mounted  
Type of fastening Snap mounting (engagement)  
Material Plastic  
Material quality Thermoplastic  
Halogen free Yes  
Surface protection Lacquered  
Surface finishing Glossy  
Antimicrobial treatment No  
With loop through function Yes  
With on/off switch No  
Colour of switch operator Aluminium  
Rotated central insert No  
Nominal current 16 A  
Nominal voltage 250 V  
Frequency 50-60 Hz  
Suitable for degree of protection (IP) IP20  
Degree of impact strength (IK) IK00  
Device width 44 mm  
Device height 44 mm  
Device depth 41.5 mm  
Min. depth of built-in installation box 40.5 mm  
Compatible with Apple HomeKit No  
Compatible with Amazon Alexa No  
Compatible with Google Assistant No  
IFTTT support available No  
With Wi-Fi signal repeater No  
With built-in bluetooth speaker No  
For heavy conditions according to VDE No  
Built-in depth 30.5 mm  
Operating / setting temperature -5-35 °C  
Storage temperature -5-35 °C  
Voltage type AC  
Power Delivery No  
Cable nature for connection Flexible or rigid  
Cable section 2.5-2.5 mm<sup>2</sup>  
Cable support Other  
Assembly arrangement Basic element with central cover plate  
Connected object No. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.  
Pret: 69,69 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-2p-t-16a-250vca-std-fr-port-eticheta-living-light-tech-2-module>