



### **BTICINO AXOLUTE - DESCARCATOR DE SUPRATENSIUNE 230V**

Descoperiți Axolute - descărcător de supratensiune 230V din categoria Prize, Intrerupatoare & Doze - Doza modulara, un produs cu codul HC4536. Acesta oferă caracteristici excelente: Nominal voltage AC 230 V

Max. continuous voltage AC 250 V

Nominal load current 16 A

Nominal discharge surge current (8/20) (L-N) 1 kA

Total discharge current (8/20) (L+N-PE) 2 kA

Voltage protection level 1 kV

Number of poles 1

Mounting method Module

Max. conductor cross section solid (solid, stranded) 2.5 mm<sup>2</sup>

Max. conductor cross section flexible (fine-strand) 2.5 mm<sup>2</sup>

With remote signalling contact No

Signalling at the device Optical

Category type 3 No

With interference suppressor filter No

Degree of protection (IP) IP20

Width 22.3 mm

Height 45 mm

Depth 36.3 mm

Built-in depth 36.3 mm

Degree of impact strength (IK) Not applicable

Operating / setting temperature -5-50 °C

Storage temperature -10-70 °C

Connection type Screwed terminal. Ideal pentru proiectele tale, asigurand eficiență și calitate superioară.

Pret: 187,45 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/axolute-descarcator-de-supratensiune-230v>