



LEGRAND BLOC DIF. ADAPTAT DX³-SURUB-4P-400V~63A-TIPHPI-1000MA SELEC.-DISJ. 1MODUL/POL-FIR TRAD.

Descoper? Bloc dif. adaptat DX³-urub-4P-400V~63A-tipHpi-1000mA selec.-disj. 1modul/pol-fir trad. din categoria Sigurante automate - Tetrapolare cu protectie diferentiala, un produs cu codul 410560. Acesta ofer? caracteristici excelente: Nominal voltage 250-440 V

Nominal current 63 A

Rated fault current adjustable No

Rated fault current 1-1 A

Max. delay time 40 ms

Delay adjustable No

Number of poles 4

Leakage current type F

Frequency 50 Hz

Rated insulation voltage U_i 500 V

Rated impulse withstand voltage U_{imp} 4 kV

Connectable conductor cross section solid-core 1.5-35 mm²

Connectable conductor cross section multi-wired 1.5-25 mm²

Anti- nuisance tripping version Yes

With interlocking device Yes

Degree of protection (IP) IP20

Pollution degree 2

Ambient temperature during operating -25-70 °C

Width 124.6 mm

Height 96 mm

Depth 78 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Voltage type AC

Terminal marking indication Yes

Colour Green/yellow

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Cable

Mounting method DIN rail

Connected object No

Application store for download Not applicable. Ideal pentru proiectele tale, asigurand eficient?? ?i calitate superioar?.

Pret: 365,18 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/bloc-dif-adaptat-dx3-surub-4p-400v-63a-tiphpi-1000ma-selec-disj-1modul-pol-fir-trad>