



LEGRAND BLOC DIFERENTIAL DX3 4P 63A A 100MA

Descoper? Bloc diferen?ial DX3 4P 63A A 100mA din categoria Sigurante automate - Tetrapolare cu protectie diferentiala, un produs cu codul 410509. Acesta ofer? caracteristici excelente: Nominal voltage 250-440 V

Nominal current 63 A

Rated fault current adjustable No

Rated fault current 0.1-0.1 A

Max. delay time 0 ms

Delay adjustable No

Number of poles 4

Leakage current type A

Frequency 50 Hz

Rated insulation voltage U_i 500 V

Rated impulse withstand voltage U_{imp} 4 kV

Connectable conductor cross section solid-core 1.5-35 mm²

Connectable conductor cross section multi-wired 1.5-25 mm²

Anti- nuisance tripping version No

With interlocking device Yes

Degree of protection (IP) IP20

Pollution degree 2

Ambient temperature during operating -25-70 °C

Width 124.6 mm

Height 96 mm

Depth 78 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Voltage type AC

Terminal marking indication Yes

Colour Green/yellow

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Cable

Mounting method DIN rail

Connected object No

Application store for download Not applicable. Ideal pentru proiectele tale, asigurand eficienta si calitate superioara?.

Pret: 404,59 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/bloc-diferential-dx3-4p-63a-a-100ma>