



LEGRAND DISJUNCTOR DX³-2P-230/400V~2,5A-25KA-DOAR MAGNETIC - 2M

Descoper? Disjuncteur DX³-2P-230/400V~2,5A-25kA-doar magnetic - 2M din categoria Sigurante automate - Bipolare, un produs cu codul 409867. Acesta ofer? caracteristici excelente: Built-in depth 44 mm

Release characteristic MA

Number of poles (total) 2

Number of protected poles 2

Rated current 2.5 A

Rated voltage 400 V

Rated insulation voltage U_i 500 V

Rated impulse withstand voltage U_{imp} 4 kV

Voltage type AC

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V 50 kA

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V 25 kA

Frequency 50-60 Hz

Flush-mounted installation Yes

Concurrently switching neutral conductor No

Pollution degree 3

Additional equipment possible Yes

Width in number of modular spacings 2

Degree of protection (IP) IP20

Ambient temperature during operating -25-70 °C

Connectable conductor cross section multi-wired 1.5-25 mm²

Connectable conductor cross section solid-core 1.5-35 mm²

Explosion-proof No

Width 35.4 mm

Height 94.8 mm

Depth 77.8 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Nominal voltage 360-440 V

Electric supplying direction By the top or bottom

Terminal marking indication No

Colour Grey

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Busbar and cable

Label space/information surface Yes

Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficienta si calitate superioara.

Pret: 187,93 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctori-dx3-2p-230-400v-2-5a-25ka-doar-magnetic-2m>