



### **LEGRAND DISJUNCTOR TX3 2P B8 6KA**

Descoper? Disjuncteur TX3 2P B8 6kA din categoria Sigurante automate - Bipolare, un produs cu codul 403384. Acesta ofer? caracteristici excelente: Built-in depth 44 mm

Release characteristic B

Number of poles (total) 2

Number of protected poles 2

Rated current 8 A

Rated voltage 400 V

Rated insulation voltage  $U_i$  500 V

Rated impulse withstand voltage  $U_{imp}$  4 kV

Rated short-circuit breaking capacity  $I_{cn}$  according to EN 60898 at 230 V 10 kA

Voltage type AC

Rated short-circuit breaking capacity  $I_{cn}$  according to EN 60898 at 400 V 6 kA

Frequency 50-60 Hz

Current limiting class 3

Flush-mounted installation Yes

Concurrently switching neutral conductor No

Pollution degree 2

Additional equipment possible Yes

Width in number of modular spacings 2

Degree of protection (IP) IP20

Explosion-proof No

Width 35.4 mm

Height 88 mm

Depth 77.8 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Nominal voltage 240-415 V

Electric supplying direction By the top or bottom

Terminal marking indication No

Colour Grey

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Busbar and cable

Label space/information surface Yes

Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.

Pret: 74,29 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctor-tx3-2p-b8-6ka>