



SCHNEIDER SEPARATOR DE SARCINA COMPACT NSX400NA - 400 A - 3 POLI

range	ComPacT new generation
product name	ComPacT NSX new generation
product or component type	Switch disconnecter
device short name	NSX400NA
poles description	3P
network type	AC
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
[Ie] rated operational current	AC-22A: 400 A AC 50/60 Hz 220...690 V AC-23A: 400 A AC 50/60 Hz 220...690 V
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3
[Ith] conventional free air thermal current	400 A at 60 °C
[Icm] rated short-circuit making capacity	330 kA with upstream protection circuit breaker 7.1 kA switch-disconnector alone
breaking capacity code	NA
suitability for isolation	Yes conforming to EN/IEC 60947-3
contact position indicator	Yes
visible break	No
utilisation category	AC-22A AC-23A
control type	Complementary Toggle
mounting mode	Fixed
mounting support	Backplate

upside connection	Front
downside connection	Front
[Icw] rated short-time withstand current	1.93 kA during 20 s conforming to IEC 60947-3 5 kA during 1 s conforming to IEC 60947-3 5 kA during 3 s conforming to IEC 60947-3
mechanical durability	15000 cycles conforming to IEC 60947-3 AC-22A: 10000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3 AC-22A: 2500 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-3 AC-22A: 5000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-3 AC-22A: 5000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-3
electrical durability	AC-23A: 10000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3 AC-23A: 2500 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-3 AC-23A: 5000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-3 AC-23A: 5000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-3
connection pitch	45 mm
height	255 mm
width	140 mm
depth	110 mm
net weight	5.2 kg
compatibility code	NSX400
standards	Environment EN/IEC 60947 UL 508
product certifications	EAC CCC
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
electrical shock protection class	Class II
pollution degree	3 conforming to IEC 60664-1
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.333 kg
Package 1 Height	15 cm
Package 1 width	16 cm
Package 1 Length	29.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Weight	11.369 kg

Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

Pret: 2.738,43 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/separator-de-sarcina-compact-nsx400na-400-a-3-poli-97484>